

# CHALLENGER SERVICES

A Subsidiary of Sol Industries LLC

## Highline Unit

## Challenger HL3



Challenger Highline Unit shown with optional tandem winch arrangement and fairleads

### Cat Challenger Series Tractor

#### Caterpillar Mobil-Track System (MTD) *The best of wheels and tracks!*

- More traction and stability than a wheel machine, yet able to travel on paved roads.
- Differential steering — provides continuous power to both track belts, even in a turn.
- Power shift transmission, with inching foot pedal, 10 forward speeds and two in reverse.
- Extremely maneuverable—can turn in its own length.
- Very mobile—capable of speeds up to 18 mph.
- Economical—rubber belts outlast tires.

#### Specifications—Tractor

Horsepower	285
Track Gauge	85 inches
Belt Width	
Standard	24.5 inches
Optional	20.5, 27.5, 35.5 inches
Length of track on ground	8 ft. 11 in.

### Challenger Highline Attach.

#### Designed specifically for the Cat Challenger Series Tractor

- Attachment is designed for multiple winches to fit job requirements.
- Winches can range from 5,000 lbs. Up to 15,000 lbs. pull units per winch. Larger units also available.
- Highline attachment retains drawbar for heavy jobsite pulling.
- Entire Highline package (excluding any options) is easily installed and removed.
- Winches can be equipped with or without fairleads.
- Superb low ground pressure while maintaining good anchor weight. Empty ground pressure 8.8 PSI (with 35.5 inch belts).
- Excellent operator visibility and comfort.