

D6E Auto 400 Welder Tractor



Caterpillar D6E Tractor
Shown with (5) Miller XMT 350 welders



Lincoln DC-400 Welders

Arrangement Includes:

- Four (4) Lincoln Idealarc DC-400 rectifier welders.
- Newage alternator with low frequency shut off.
- Quincy 350 compressor—Electric motor-2 stage. Maximum intermitten pressure 350 psi (37 dfm) FAD @ 940 rpm
- 120 gallon air receiver from 250—300 psi
- Four (4) 60 hz 110 volt electrical outlets.

These welder arrangements can be installed on a **Cat D6D, D6E, D7G, Dressta TD15, TD20 or Komatsu D85 tractor.**



Dimensions:

Overall Length: 18' 8"
Overall Width: 8' 4"
Overall Height: 10' 1"
Shipping Weight: 39,000 lbs.

Performance:

- 400 amp output at 100% duty cycle (each welder).
- Current range 6-500 amps.

Features:

- Constant voltage/constant current for:
 - Innershield self-shielding flux cored arc welding.
 - Outershield gas shielded flux cored arc welding.
 - Gas metal arc welding.
 - Submerged arc welding.
 - Air carbon gouging-up to 8 mm carbons.
 - Stick welding.
 - TIG welding.
- Fully compatible with automatic and semi-automatic remote wire feeders.
- Versatility and top quality performance.
- No surging when other welders start and stop.

Options:

Hiab 060 or 090 Knuckleboom
Hydraulically operated stiff boom
50 Hz system
Miller XMT 350 welders
Quincy 390 compressor
Volt and amperage gauges
120 gallon air tank