

# **Pipelayer Attachment**

Model CP572G Hydraulic Pipelayer Attachment

Designed for mounting on Dressta TD20H LGP Tractor Komatsu D85PX-15 Tractor Caterpillar D7G LGP Tractor

#### Designed to ANSI B30.14 Standards

The Challenger Services CP572G pipelayer is very easy to operate with a minimum amount of training needed This unit has infinitely variable line speeds with an optional free fall on the load line.

Both load line and boom line winches provide smooth, precise load control during operation. All hydraulics used to operate the sideboom and attachments are plumbed through the tractor. This feature alone makes the unit more cost efficient and enhances operational safety.



## **Attachment Specifications**

Lift Capacity Load Line Hoist	90,000 lbs. (40,824 kg) 2 speed
Hook Speed	4 part line High: 43 fpm (13.1 m/m) Low: 21 fpm
Cable diameter	7/8" (22.23 mm)
Boom Line Hoist	1 speed
	3 part line
Winch Brakes	Automatic, multiple oil
	disc, spring applied,
	hydraulic release
Boom Length Unattached	20 ft (6.10 m)
Boom Length Attached	23 ft (7.01 m)

### **Shipping Weight:**

 Boom
 2,018 lbs. (915 kg)

 Pipelayer Attachment
 14,200 lbs. (6,441 kg)

 Counterweights
 10,720 lbs. (4,863 kg)

 Total Weight
 26.938 lbs. (12,219 kg)



## **Pipelayer Specifications**

i ipolayor opooriioationo	
Horsepower	200–240
Track Gauge	84-89 in. (2.13 m-2.26 m)
Width	11 ft. 11 in. (3.38 m)
Width with CWT Extended	17 ft. 1 in. (4.91 m)
Length	13 ft. 10 in.–14 ft. 3 in.
	(3.94 m-4.34 m)
Length with bumper	15 ft.–15 ft. 5 in.
	(4.57 m-4.88 m)
Height to Top of Cwt	9 ft. 7 in. (2.67 m)
Height to Top of Stack	11 ft. 2 in.–11 ft. 10 in.
	(3.13 m-3.63 m)
Track Shoe Width	26 in.—36 in. (.66 m—.91m)
Track Length	10 ft. 10 in.–11 ft. 5 in.
	(3.30 m-3.48 m)
Shipping Weight	61,045 lbs (27,690 kg)

#### **Options:**

Boom Extension-8 ft.

Phone: (918) 447-0055

Fax: (918) 447-0067

Fall-off Shipping Weight Total Operating Weight

Folding Boom—Convenient for clearing under power lines.

CHALLENGER SERVICES 4530 South Jackson Avenue Tulsa, Oklahoma 74107 USA email: sales@challengerservices.com www.challengerservices.com

10,938 lbs. (4,961 kg)

69,000–75,000 lbs. (32,651–34,091 kg)